

PIGMENT PASTA

Color Additive

DESCRIPTION AND BASIC PROPERTIES

Color pigment for polyester materials in the form of paste, consist of a mixture of pigments and inerts thinners, surfactants. Also contains organic and inorganic pigments and polyester. Depending on color variation polyester resin may vary from 35 to 50 percent, while pigment concentration is 55 to 70 percent.

* This information has been prepared by considering the general conditions. Problems arising due to inadequacy of information ESKİM A.Ş. Is not responsible.

PROPERTIES OF LIQUID FORM

	UNIT	VALUE	METOD
Appearance		Vary	
Viscosity¹	cp	70000	ISO 2555
Monomer Content	%	20 ± 0.5	ISO 3251
Shelf Life	month	24	
¹ Brookfield DV II, 23°C, 3 spd, 10 rpm			

STORAGE CONDITIONS

It should be stored in a dry, clean and cool place (15-25 ° C) in closed packages. The shelf life of the product is valid for this temperature range and it should not be forgotten that it will shorten at high temperatures. Products with the same charge number and date must be stored together.

Another factor that affects the life of unsaturated polyester resins containing styrene is sunlight. Styrene must be polymerized in the sunlight and products that are considered to shorten the life of the product should be avoided from direct sunlight contact.

MORE INFORMATION

ESKİM KİMYA
Organize Sanayi Bölgesi 6. Cad. No:2 26110 ESKİŞEHİR
TEL:0(222) 236 01 90 (PBX)
FAKS: 0(222) 236 01 87

<http://www.eskim.com.tr>